

Project	Hywind-class FPSO — topside process module M-42	Area	M-42 / EL bulk
Client	Havlinjen Energi AS	Enquiry	RFQ-2026-0411 (cable support & containment)
Environment	Offshore, splash-zone exposed — 316L preferred unless noted	Standard	IEC 61537, NORSOK M-501 coatings

Cable management & support — bill of materials

ITEM	DESCRIPTION	MATERIAL / FINISH	QTY	UNIT
1	Cable ladder, 600 mm wide, 6 m length	316L stainless	80	ea
2	Cable ladder, 300 mm wide, 6 m length	316L stainless	120	ea
3	Cable ladder, 450 mm wide, 6 m length	Hot-dip galvanised	60	ea
4	Flat elbow 90°, for 300 mm cable ladder	316L stainless	40	ea
5	Cable tray, return-flange, 200 mm, 3 m	316L stainless	240	ea
6	Cable tray, 100 mm, 3 m	Hot-dip galvanised	180	ea
7	Support channel, Mekano CH50, 3 m	316L stainless	150	ea
8	Strut channel, Unistrut P1000, 41×41, 3 m	Stainless steel	200	ea
9	Tube clamp, ETIN-S, 20 mm O.D.	Stainless steel	600	ea
10	Tube clamp, Stauff DIN 3015 series 2, 22 mm O.D.	316L stainless	300	ea
11	Cable cleat, SmartCleit trefoil, 40 mm cable	316L stainless	500	ea
12	Hexagon bolt M10×20 with flange nut	A4 stainless	2000	pcs

Notes. (1) Substitution permitted with technically-equivalent product subject to client approval — state proposed make/part and load class. (2) All ladder/tray to be supplied with matching couplers and fixings. (3) Competitor references (Unistrut, Stauff) are for sizing only; equivalent offered product acceptable. (4) Prices to be quoted per unit, NOK, ex-works, with lead time.